

IPW

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE


In re Application of

Katsuhiro YADA

Application No.: 10/551,474

Filed: September 30, 2005

For: OPTICAL COMMUNICATION SYSTEM HAVING OPTICAL AMPLIFICATION
FUNCTION



Customer Number: 20277

Confirmation Number: 4393

Group Art Unit: 2613

Examiner: Not yet assigned

REQUEST FOR CORRECTED FILING RECEIPT

Mail Stop OFR
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

Attached is a copy of the Filing Receipt received from the U.S. Patent and Trademark Office in the above-referenced application. It is noted that the **total number of claims is listed incorrectly**. Attached is a copy of the claims as filed, which evidences that **the total number of claims should be 26**. It is requested that a corrected filing receipt be issued.

Respectfully submitted,

McDERMOTT WILL & EMERY LLP

Ben K. Lind Reg. No. 51,321

for: Stephen A. Becker
Registration No. 26,527

600 13th Street, N.W.
Washington, DC 20005-3096
Phone: 202.756.8000 SAB:ln
Facsimile: 202.756.8087
Date: February 20, 2007

Please recognize our Customer No. 20277
as our correspondence address.



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
 United States Patent and Trademark Office
 Address: COMMISSIONER FOR PATENTS
 P.O. Box 1450
 Alexandria, Virginia 22313-1450
 www.uspto.gov

APPL NO.	FILING OR 371 (c) DATE	ART UNIT	FIL FEE REC'D	ATTY. DOCKET NO	DRAWINGS	TOT CLMS	IND CLMS
10/551,474	09/30/2005	2613	2460	051023-0027	26 ← 27	3	3

CONFIRMATION NO. 4393

20277
 McDERMOTT WILL & EMERY LLP
 600 13TH STREET, N.W.
 WASHINGTON, DC 20005-3096

RECEIVED
 OCT 10 2006

FILING RECEIPT



OC000000020635817

McDermott Will & Emery LLP
 DC Office

Date Mailed: 10/05/2006

Receipt is acknowledged of this regular Patent Application. It will be considered in its order and you will be notified as to the results of the examination. Be sure to provide the U.S. APPLICATION NUMBER, FILING DATE, NAME OF APPLICANT, and TITLE OF INVENTION when inquiring about this application. Fees transmitted by check or draft are subject to collection. Please verify the accuracy of the data presented on this receipt. If an error is noted on this Filing Receipt, please mail to the Commissioner for Patents P.O. Box 1450 Alexandria Va 22313-1450. Please provide a copy of this Filing Receipt with the changes noted thereon. If you received a "Notice to File Missing Parts" for this application, please submit any corrections to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections (if appropriate).

Applicant(s)

Katsuhiko Yada, Osaka, JAPAN;

Power of Attorney: The patent practitioners associated with Customer Number 20277.

Domestic Priority data as claimed by applicant

This application is a 371 of PCT/JP04/04664 10/21/2004

Foreign Applications

JAPAN 2003-099570 04/02/2003
 JAPAN 2003-110699 04/15/2003

Projected Publication Date: 01/04/2007**Non-Publication Request:** No**Early Publication Request:** No**Title**

Optical communication system having optical amplification function

Preliminary Class

398

PROTECTING YOUR INVENTION OUTSIDE THE UNITED STATES

Since the rights granted by a U.S. patent extend only throughout the territory of the United States and have no effect in a foreign country, an inventor who wishes patent protection in another country must apply for a patent in a specific country or in regional patent offices. Applicants may wish to consider the filing of an international application under the Patent Cooperation Treaty (PCT). An international (PCT) application generally has the same effect as a regular national patent application in each PCT-member country. The PCT process **simplifies** the filing of patent applications on the same invention in member countries, but **does not result** in a grant of "an international patent" and does not eliminate the need of applicants to file additional documents and fees in countries where patent protection is desired.

Almost every country has its own patent law, and a person desiring a patent in a particular country must make an application for patent in that country in accordance with its particular laws. Since the laws of many countries differ in various respects from the patent law of the United States, applicants are advised to seek guidance from specific foreign countries to ensure that patent rights are not lost prematurely.

Applicants also are advised that in the case of inventions made in the United States, the Director of the USPTO must issue a license before applicants can apply for a patent in a foreign country. The filing of a U.S. patent application serves as a request for a foreign filing license. The application's filing receipt contains further information and guidance as to the status of applicant's license for foreign filing.

Applicants may wish to consult the USPTO booklet, "General Information Concerning Patents" (specifically, the section entitled "Treaties and Foreign Patents") for more information on timeframes and deadlines for filing foreign patent applications. The guide is available either by contacting the USPTO Contact Center at 800-786-9199, or it can be viewed on the USPTO website at <http://www.uspto.gov/web/offices/pac/doc/general/index.html>.

For information on preventing theft of your intellectual property (patents, trademarks and copyrights), you may wish to consult the U.S. Government website, <http://www.stopfakes.gov>. Part of a Department of Commerce initiative, this website includes self-help "toolkits" giving innovators guidance on how to protect intellectual property in specific countries such as China, Korea and Mexico. For questions regarding patent enforcement issues, applicants may call the U.S. Government hotline at 1-866-999-HALT (1-866-999-4158).

LICENSE FOR FOREIGN FILING UNDER Title 35, United States Code, Section 184 Title 37, Code of Federal Regulations, 5.11 & 5.15

GRANTED

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" followed by a date appears on this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.15. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.

This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related applications(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the national security or the export of technical data. Licensees should apprise themselves of current regulations

especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR 121-128)); the Bureau of Industry and Security, Department of Commerce (15 CFR parts 730-774); the Office of Foreign Assets Control, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

NOT GRANTED

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" DOES NOT appear on this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).

**CLAIMS:**

1. An optical communications system in which a base station and a local station are connected using an optical fiber, the optical communications system being characterized in that

a wavelength of a light source for a signal that generates downstream signal light is set to a wavelength with an effect of Raman amplifying an upstream light signal that propagates through the optical fiber, and an upstream light signal transmitted between the base station and the local station is amplified in the optical fiber while the upstream light signal is propagating through the optical fiber.

2. The optical communications system according to Claim 1, wherein

a high nonlinearity fiber is used for at least part of the optical fiber.

3. The optical communications system according to Claim 1 or 2, wherein

light that is switched ON and OFF is used as the downstream signal light, and a modulation method, by which an ON state and an OFF state transit even when coded data is a sequence of 0's and the ON state and the OFF state transit even when the coded data is a sequence of 1's, is used as a modulation method for the downstream signal light.

4. The optical communication system according to Claim 3, wherein

in the backbone optical fiber, a length of a portion where upstream signal light is amplified is of a distance longer than a length of the optical fiber corresponding to a set of the ON state and the OFF state of the downstream signal light.

5. The optical communication system according to any of Claims 1 through 4, wherein

the base station is provided with an optical filter used to select a wavelength of light coming incident on a light-receiving element.

6. A PON (Passive Optical Network) system in which a base station and an optical branching station equipped with a passive optical divider are connected using a backbone optical fiber, and the optical branching station and plural local stations are connected individually using branch optical fibers, the PON system being characterized in that

a wavelength of a light source for a signal that generates downstream signal light is set to a wavelength with an effect of Raman amplifying an upstream light signal that propagates through the backbone optical fiber, and an upstream light signal transmitted between the base station and each local station is amplified in the backbone optical fiber while the

upstream light signal is propagating through the backbone optical fiber.

7. The PON system according to Claim 6, wherein a high nonlinearity fiber is used for at least part of the backbone optical fiber.

8. The PON system according to Claim 6 or 7, wherein light that is switched ON and OFF is used as the downstream signal light, and a modulation method, by which an ON state and an OFF state transit even when coded data is a sequence of 0's and the ON state and the OFF state transit even when coded data is a sequence of 1's, is used as a modulation method for the downstream signal light.

9. The PON system according to Claim 8, wherein in the backbone optical fiber, a length of a portion where upstream signal light is amplified is of a distance longer than a length of the backbone optical fiber corresponding to a set of the ON state and the OFF state of the downstream signal light.

10. The PON system according to any of Claims 6 through 9, wherein

the light source for a signal and an optical multiplexer/demultiplexer are provided in the base station,

and light for a signal is pumped into the backbone optical fiber from the base station toward the optical branching station by way of the optical multiplexer/demultiplexer.

11. The PON system according to any of Claims 6 through 10, wherein

a star coupler is used as the passive optical divider.

12. The PON system according to any of Claims 6 through 10, wherein

as the passive optical divider, a star coupler is used for the downstream signal light, and an AWG (Arrayed-Waveguide Grating) capable of multiplexing and demultiplexing upstream signal light using a difference in wavelength is used for the upstream signal light.

13. A PON (Passive Optical Network) system in which a base station and an optical branching station equipped with a passive optical divider are connected using a backbone optical fiber, and the optical branching station and plural local stations are connected individually using branch optical fibers, the PON system being characterized by comprising:

a light source for amplification that generates light for amplification having a wavelength with an effect of amplifying a light signal propagating through an optical fiber

(including a backbone optical fiber and a branch optical fiber, and the same applies hereinafter); and

an optical multiplexer/demultiplexer used to pump the light for amplification into the optical fiber,

wherein, in the optical fiber, a light signal transmitted between the base station and each local station is amplified while the light signal is propagating through the optical fiber.

14. The PON system according to Claim 13, wherein Raman amplification is used as a function of amplifying a light signal, and the light for amplification propagates in a direction opposite to the signal light.

15. The PON system according to Claim 13 or 14, wherein a high nonlinearity fiber is used.

16. The PON system according to Claim 13, wherein an erbium-doped fiber (EDF) is used as a function of amplifying the light signal, and the signal for amplification is in the same direction as the signal light.

17. The PON system according to Claim 13, wherein the light source for amplification and the optical multiplexer/demultiplexer are provided in the base station,

and the light for amplification is pumped into the backbone optical fiber from the base station toward the optical branching station.

18. The PON system according to Claim 13, wherein the light source for amplification and the optical multiplexer/demultiplexer are provided in the optical branching station, and the light for amplification is pumped into the backbone optical fiber from the optical multiplexer/demultiplexer toward the base station.

19. The PON system according to Claim 17, wherein a second optical multiplexer/demultiplexer, a third optical multiplexer/demultiplexer, and an optical path connecting the second optical multiplexer/demultiplexer and the third optical multiplexer/demultiplexer are provided in the optical branching station,

the light for amplification that travels through a backbone optical fiber for an upstream signal is extracted from the second optical multiplexer/demultiplexer to be supplied to the third optical multiplexer/demultiplexer via the optical path, and

the light for amplification is pumped into a backbone optical fiber for a downstream signal from the third optical multiplexer/demultiplexer toward the base station.

20. The PON system according to Claim 13, wherein the light source for amplification and the optical multiplexer/demultiplexer are provided in the optical branching station, and the light for amplification is pumped into the branch optical fiber by way of the passive optical divider toward the local station.

21. The PON system according to Claim 13, wherein the light source for amplification and the optical multiplexer/demultiplexer are provided in the base station, and the light for amplification is pumped into the backbone optical fiber from the base station toward the optical branching station, and

a reflector that allows the light for amplification to undergo total reflection to the backbone optical fiber is provided in the optical branching station.

22. The PON system according to Claim 13, wherein the light source for amplification and the optical multiplexer/demultiplexer are provided in the base station, and the light for amplification is pumped into the backbone optical fiber from the base station toward the optical branching station,

a second optical multiplexer/demultiplexer and a

reflector are provided in the optical branching station, and the light for amplification that travels through the backbone optical fiber is extracted from the second optical multiplexer/demultiplexer, so that the light for amplification is allowed to undergo total reflection on the reflector.

23. The PON system according to Claim 13, wherein the optical multiplexer/demultiplexer is provided in the optical branching station;

an optical fiber is provided between the base station and the optical branching station besides the backbone optical fiber, and

the light source for amplification is provided in the base station, and the light for amplification is supplied to the optical multiplexer/demultiplexer via the optical fiber, so that the light for amplification is pumped into the backbone optical fiber from the optical multiplexer/demultiplexer toward the base station.

24. The PON system according to any of Claims 17 through 23, wherein

a star coupler is used as the passive optical divider.

25. The PON system according to Claim 13, wherein

an optical fiber is provided between the base station and the optical branching station besides the backbone optical fiber, and

the light source for amplification is provided in the base station, so that the light for amplification is pumped into one optical path of the optical multiplexer/demultiplexer on the local station side via the optical fiber toward the base station.

26. The PON system according to any of Claims 17 through 23 and 25, wherein

an AWG (Arrayed-Waveguide Grating) capable of multiplexing and demultiplexing light using different wavelengths is used as the passive optical divider.